

SPRUNG FLOOR:INFINITY ACHILLE

SPRUNG FLOOR, BIRCH PLYWOOD PANELS COUPLED WITH A SPRUNG SUPPORT MADE OF PATENTED ELASTOMER BLOCKS AND TREATED WITH WATER REPELLENT MATERIAL FOR OUTDOORS

INFINITY ACHILLE Infinity Achille is composed of birch panels which are crafted and coupled with the sprung support system. Suitable for all types of dances, included the percussive dances (tap, flamenco, character) and treated with water repellent material, it is the best suited for touring companies. Available only in the removable version, with a tongue and groove system (aluminium tongue), "dovetail joint"

PANELS

Thickness	1,8 cm
Measure	150 x 75 cm
Removable version	tongue and groove system (aluminium tongue), "dovetail joint"
Fire reaction	Class 1 CFL-s1



ELASTOMER BLOCKS

Thickness	1,8 cm
Measure	5 x 5 cm
Quantity of blocks per panel	24
Fire reaction	Self-extinguishing

INFINITY ACHILLE COMPLIES WITH EUROPEAN REGULATION (EN 14904), CE MARK

DESCRIPTION	REGULATION REF.	PERFORMANCE
Friction coefficient	EN 13306-4	93
Shock absorption	EN 14808	71%
Vertical deformation	EN 14809	4,3 mm
Rebound	EN 12235	90%
Fire reaction	EN 13501-1	Cfl-s1

Please note: each panel has a grain and shade of its own colour



REGISTERED OFFICE
Via Monza, 10 Lissone (MB)

OPERATIONAL HEADQUARTERS
Via Corino, 30 LISSONE



800400463



info@antheopavimentidanza.it



[ANTHEOpavimentidanza](https://www.facebook.com/ANTHEOpavimentidanza)



[antheo.pavimentidanza](https://www.instagram.com/antheo.pavimentidanza)