

INFINITY EVOLUTION SPRUNG DANCE FLOOR

SPRUNG FLOOR OF MULTILAYER BIRCH PANELS ON A
SHOCK ABSORPTION SYSTEM MADE OF PATENTED ELASTOMER BLOCKS.

INFINITY EVOLUTION has the same features as the Infinity series, but with the surface made of oak slats or kind of wood chosen by customer, thickness of 3 mm and each piece glued separately on the multilayer birch panel.

PANELS

Thickness	2,1 cm
Size	150 x 75 cm
Permanent Installation	Slot-in joint system
Portable Installation	By hook system - "dovetail-joint"
Fire Reaction	Class 1 CFL-s1



ELASTOMER BLOCKS

Thickness	1,8 cm
Size	5 x 5 cm
Quantity of blocks per panel	24
Fire reaction	Self-extinguishing

INFINITY EVOLUTION COMPLIES WITH EUROPEAN REGULATION (EN 14904), CE MARK

DESCRIPTION	REGULATION REF.	PERFORMANCE
Friction coefficient	EN 13306-4	93
Shock absorption	EN 14808	71%
Vertical deformation	EN 14809	4,3 mm
Rebound	EN 12235	90%
Fire reaction	EN 13501-1	Cfl-s1

Please note: each panel has a grain and shade of its own colour



REGISTERED OFFICE
Via Monza, 10 Lissone (MB)

**OPERATIONAL
HEADQUARTERS**
Via Corino, 30 LISSONE



800400463



info@antheopavimentidanza.it



[ANTHEOpavimentidanza](https://www.facebook.com/ANTHEOpavimentidanza)



[antheo.pavimentidanza](https://www.instagram.com/antheo.pavimentidanza)