

DANCE FLOOR: NICE

SPRUNG FLOOR OF MULTILAYER BIRCH PANELS ON A SHOCK ABSORPTION SYSTEM MADE OF PATENTED ELASTOMER BLOCKS.

NICE is composed of birch panels coupled with a shock absorption system made of elastomer blocks. No risk of delamination. Finishing with coating products suitable for dance. Perfect grip on a wooden sprung floor.

PANELS

Thickness	1,8 cm
Size	150 x 75 cm
Permanent installation	Slot-in joint system
Portable installation	By hook system - "dovetail-joint"
Fire reaction	Class 1 CFL-s1



ELASTOMER BLOCKS

Thickness	1,8 cm
Size	5 x 5 cm
Quantity	24
Fire reaction	Self-extinguishing

INFINITY NAKED COMPLIES WITH EUROPEAN REGULATION (EN 14904), CE MARK

DESCRIPTION	REGULATION REF.	PERFORMANCE
Friction coefficient	EN 13306-4	93
Shock absorption	EN 14808	67%
Vertical deformation	EN 14809	4,3 mm
Rebound	EN 12235	90%
Fire reaction	EN 13501-1	Cfl-s1

Please note: each panel has a grain and shade of its own colour



REGISTERED OFFICE
Via Monza, 10 Lissone (MB)

OPERATIONAL HEADQUARTERS
Via Corino, 30 LISSONE



800400463



info@antheopavimentidanza.it



[ANTHEOpavimentidanza](https://www.facebook.com/ANTHEOpavimentidanza)



[antheo.pavimentidanza](https://www.instagram.com/antheo.pavimentidanza)